



TWO-WAY RADIO ANTENNAS



FEATURES

- Emergency, commercial, amateur applications
- Flexible design for easy installation
- Motorola-style NMO mount nut
- Compatible with all 1-1/8" -18 thread mounts
- Includes rubber seal gasket against water leakage

Antenna Model

HCQ152	152-162 MHz 18-3/8" Whip
HCQ450	450-470 MHz 6-3/8" Whip

SPECIFICATIONS

- | | |
|-----------------------|---------------------------------|
| • 1/4 Wave | • Brass Nut Plated with Zinc |
| • Unity Gain | • Silver Plated Contact Center |
| • VSWR < 1.5:1 | • Stainless Steel Radiation Rod |
| • Max Power 150 Watts | • Nominal Impedance 50 ohms |

UHF (450-470 MHz)
VHF (152-162 MHz)



HCQ152 HCQ450



PROFESSIONAL MOUNT ACCESSORIES

HCTSS NMO TRUNK LID MOUNT

- Mounts on edge
- No drilling into the vehicle
- 17' RG-58A/U coax
- PL-259
- Zinc plated brass



HCTSS

HCMM3 NMO MAGNETIC MOUNT

- Mounts on roof top surface
- No drilling into the vehicle
- 3.4" diameter magnetic mount
- Strong magnetic force
- 12' RG-58A/U coax
- PL-259
- Chrome plated brass
- Engineered for high speed vehicles



HCMM3

HCNMO34 NMO HOLE MOUNT

- 3/4" hole mount size
- No cable, no connector
- Large center pin
- Ideal for 30 - 1000 MHz
- Brass nut
- Precise tooling parts



HCNMO34



Connector and coax cable
sold separately

*Contact your Holzberg authorized two-way
radio dealer:*



P.O. Box 322, Totowa, NJ 07511
Phone: 1-800-654-9550 • 973-389-9600
Fax: 973-389-9696
E-Mail: holzberg@juno.com
Website: www.holzberg.com